

# 3G Data Card



## Features

- Chip: Nufront Telink7619
- 2G/3G: WCDMA and GSM
- Band: GSM850/900/1800/1900+WCDMA 2100
- Rate: Downlink 14.4Mbps and uplink 5.76Mbps
- Card Type: USB
- Size: 90x27x12mm
- Support multiple languages

### Hardware Description

Chip	Telink7619
Highest Transmission Speed	Downlink 14.4Mbps/ Uplink 5.76Mbps
Receiving Sensitivity	<-102dBm
Running Temperature	-20°C - +55°C
Storing Temperature	-30°C - +65°C
Constant Humidity and Heat Test Standard	40°C/93%

### Structure Description

Size	90x27x12mm
Appearance	USB Modem
Shell Material	Plastic
Antenna Type	Built-in
Signaling Light	Yes

### Software Description

<b>Contact Book</b>	
Quantity	1000(PC)+USIM
Quick Search	Support
Copy	Copy from USIM to PC and PC to USIM
Storing Location	USIM and PC
<b>Message</b>	
Quantity	500(PC)+USIM
Long Message	Support
Storing Location	PC and USIM
<b>Network Function</b>	
Network Choosing	Auto network searching
Priority Network	Support
<b>Traffic Control</b>	
Data Connectivity Speed and Traffic Counting	Support
Data Connectivity Duration Presentation	Support
Data Presentation in Fixed Time and Record Deletion	Support
<b>PC Voice Function</b>	
PC Interface Dial	Support
Volume Adjustment	Support
Mic Mute Setting	Support
Number Identification	Support
<b>Call Record</b>	
Dial in, Dial out and Missed Call Record	Support
Re-dial call, send text message and save number in call record	Support
Call Record Deletion	Support
<b>USSD Function</b>	
USSD Order Compilation and Send Interface	Support
<b>OS</b>	
Support PC OS	Windows®2000/XP/Vista/Win7/Win8, MAC10.6/10.7/10.8, Linux Ubuntu